



**INDEPENDENT  
DEHUMIDIFICATION**



**TURBO  
COOLING**



**ECO  
MODE**



**HIDDEN  
DISPLAY**



**SLEEP  
MODE**

Model		PTG12KCH	
Power Supply		V-Ph-Hz	220-240V-1-50Hz
Cooling	Cooling Capacity	BTU	12000
	Cooling Power Input	W	1200
	Cooling Current Input	A	5.3
	EER	W/W	2.92
Heating	Heating Capacity	BTU	12000
	Heating Power Input	W	1190
	Heating Current Input	A	5.2
	COP	W/W	3.11
Max. input consumption		W	1500
Max. current		A	8.4
Refrigerant type/weight		g	R410A/710g
Indoor Unit	Indoor Air Circulation	m <sup>3</sup> /h	600
	Indoor Noise Level dB	dB (A)	29-40
	Net Dimension (LxWxH)	mm	780x280x208
	Packing Dimension (LxWxH)	mm	860x366x276
	Net/Gross Weight	Kg	10/12
Outdoor Unit	Compressor		GREE
	Outdoor Noise Level dB	dB (A)	52 dB(A)
	Net Dimension (LxWxH)	mm	728x262x540
	Packing Dimension (LxWxH)	mm	870x370x595
	Net/Gross Weight	Kg	26/30
	Refrigerant Type/Weight	g	R410A/710g
	Design Pressure (Hi/Low)	MPa	4.2/1.2
Connection	Liquid side / Gas Side	mm	φ6.0 / φ9.52