



**INDEPENDENT
DEHUMIDIFICATION**



**TURBO
COOLING**



**ECO
MODE**



**HIDDEN
DISPLAY**



**SLEEP
MODE**

Model		PTG24KCH	
Power Supply		V-Ph-Hz	220-240v-1-50Hz
Cooling	Cooling Capacity	BTU	24000
	Cooling Power Input	W	2300
	Cooling Current Input	A	10
	EER	W/W	2.86
Heating	Heating Capacity	BTU	24000
	Heating Power Input	W	2340
	Heating Current Input	A	10.2
	COP	W/W	2.91
Max. input consumption		W	3000
Max. current		A	14.4
Refrigerant type/weight		g	R410A/1360g
Indoor Unit	Indoor Air Circulation	m3/h	1200
	Indoor Noise Level dB	dB (A)	36-46
	Net Dimension (LxWxH)	mm	950x313x240
	Packing Dimension (LxWxH)	mm	1045x403x330
	Net/Gross Weight	Kg	14/17
Outdoor Unit	Compressor		GMCC
	Outdoor Noise Level dB	dB (A)	54 dB(A)
	Net Dimension (LxWxH)	mm	835x322x546
	Packing Dimension (LxWxH)	mm	934x382x608
	Net/Gross Weight	Kg	36/40
	Refrigerant Type/Weight	g	R410A/1360g
	Design Pressure (Hi/Low)	MPa	4.2/1.2
Connection	Liquid side / Gas Side	mm	φ6.0 / φ12.0