



**INDEPENDENT
DEHUMIDIFICATION**



**TURBO
COOLING**



**ECO
MODE**



**HIDDEN
DISPLAY**



**SLEEP
MODE**

Model		PTG30KCH	
Power Supply		V-Ph-Hz	220-240-1-50Hz
Cooling	Cooling Capacity	BTU	30000
	Cooling Power Input	W	2580
	Cooling Current Input	A	11.2
	EER	W/W	3.12
Heating	Heating Capacity	BTU	30000
	Heating Power Input	W	2590
	Heating Current Input	A	11.4
	COP	W/W	3.14
Max. input consumption		W	3950
Max. current		A	17.2
Refrigerant type/weight		g	R410A/2100g
Indoor Unit	Indoor Air Circulation	m ³ /h	1350
	Indoor Noise Level dB	dB (A)	38-48
	Net Dimension (LxWxH)	mm	1055x315x240
	Packing Dimension (LxWxH)	mm	1148x400x328
	Net/Gross Weight	Kg	16/19
Outdoor Unit	Compressor		GMCC
	Outdoor Noise Level dB	dB (A)	59 dB(A)
	Net Dimension (LxWxH)	mm	880x330x650
	Packing Dimension (LxWxH)	mm	1030x445x735
	Net/Gross Weight	Kg	46/52
	Refrigerant Type/Weight	g	R410A/2100g
	Design Pressure (Hi/Low)	MPa	4.2/1.2
Connection	Liquid side / Gas Side	mm	φ9.52 / φ15.88